




technical specifications

Product Name	Tivoli / Tivoli Online / Tivoli Multiline
Product Description	Low Level Loop
Pile Yarn Description	100% Solution Dyed Nylon (Polyamide-PA)
Tile Dimensions	50 cm x 50 cm, 25 cm x 100 cm (planks)
Pile Yarn Weight	600g/m ² +/-10%
Total Weight	4050g/m ² +/-10%
Pile Height	4.0mm +/-10%
Total Thickness	6.5mm +/-10%
Gauge/ends per 10cm	1/10 th gauge 50 stitches
Tufts per m2 / Pile Density	196,500/m ² +/-10%
Backing Description	Accummen™, 75% recycled
Wear Classification	BS EN 1307 Heavy Commercial Use Class 33
Luxury Rating Class	LC2
Flammability	Euroclass Bfl-s1
Thermal Resistance	Tog Rating 0.39; ISO 8302: 0.04 m ² K/W
Castor Chair Rating	BS EN 985 Pass - suitable for continuous use
Hexapod	BS ISO 10361: Method B:2000 3 to 4
Static Loading	BS 4939: 1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum Grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4-5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN ISO 10140-3:2010 23dB
Reduction in Impact Noise at 1000Hz	BS EN ISO 10140-3:2010 35.6dB
Number Of Tiles/Planks Per Box	20 (5m ²)

For best results we recommend*



*All tiles within these designs are unique and any linear aspects may not match from one tile to the next



This floor covering was made with renewable electricity



Environmental Profiles
Scheme Certificate Number
ENP353



Certificate Number FM01440
BS EN ISO 9001:2015



Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A+ (very low-emission) to C (high-emission)



The Building Information Foundation, Finland. Certified building materials with low emission class M1

environmental information

- Burmatex products achieve either A or A+ across all the BREEAM defined building applications
For specific rating, please refer to www.breeam.co.uk
- Burmatex products qualify for SKA as they achieve one or more requested criteria
- All Burmatex carpet/carpet tile ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of Burmatex Accummen™ backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- All Burmatex products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRC2/MRC3 (Building product disclosure and optimization - environmental product declarations), MRC3/MRC4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd
Victoria Mills, The Green
Osssett, West Yorkshire
WF5 0AN
United Kingdom

T +44 (0) 1924 262 525
F +44 (0) 1924 280 033
UK email: projects@burmatex.co.uk
International email: international@burmatex.co.uk
www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE
Burmatex carpets and carpet tiles should be installed and used in full accordance with instructions at www.burmatex.co.uk and recognised trade standards.
Orders are subject to Burmatex terms and conditions of sale. See: www.burmatex.co.uk

LRV values for **tivoli**

Please note: not all colours are available in plank size

Product code tiles	Product code planks	Product colour name	CIE Y	CIE L
20201	N/A	guyana moss	9.06	36.10
20202	21102	bermuda lime	13.10	42.91
20203	21103	caicos azure	8.29	34.58
20204	21104	tortola gold	16.86	48.09
20205	21105	bahamas orange	12.50	41.99
20206	21106	green turtle	10.82	39.27
20207	21107	st lucia night	4.02	23.75
20208	21108	belize greige	12.13	41.43
20209	N/A	trinidad sea	11.39	40.24
20210	21110	bellamy red	6.35	30.27
20211	21111	barthelemy green	3.44	21.74
20212	21112	marie galante purple	5.13	27.10
20213	21113	serranilla stone	6.16	29.82
20214	21114	st martin sands	19.69	51.49
20220	21120	barbados blue	6.23	29.98
20223	N/A	nevis blue	9.82	37.52
20225	N/A	saona sage	10.77	39.19
20230	N/A	grenada grey	5.78	28.86
20242	21142	antigua steel	10.06	37.96
20245	21145	dominica dawn	11.93	41.11
20246	N/A	tobago sands	14.42	44.82
20249	21149	martinique maroon	3.96	23.55
20252	21152	nassau skies	8.30	34.60
20253	21153	key west blue	2.69	18.77
20254	21154	puerto rico purple	6.65	30.99
20258	N/A	panama brown	4.96	26.63
20259	21159	montserrat black	2.07	15.88
20260	N/A	st kitts basalt	2.91	19.68
20701	21201	multiline ibiza blue	5.57	28.30
20702	21202	multiline pacific green	8.36	34.73
20703	21203	multiline melanesia grey	8.11	34.21
20704	21204	multiline polynesia beige	13.70	43.80
20705	21205	multiline mauritius mauve	4.65	25.71
20706	21206	multiline reunion terracotta	7.70	33.36
20707	21207	multiline tenerife black	5.80	28.91
20601	N/A	online atlantic cobalt	5.16	27.19
20602	N/A	online cyclades jade	6.60	30.88
20603	N/A	online tahitian pearl	10.45	38.64
20604	N/A	online sardinian coral	5.34	27.69
20605	N/A	online pamanzi earth	9.02	36.02
20606	N/A	online baltic amber	9.24	36.44