

# Contra Ecotrust

## Product Description



**ege**

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
<b>Construction characteristics</b>		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	1/10
Pile material	DIR 96/73, 96/74	100% polyamide
Coloration	-	Continuous dyed
Backing	eTL	Ecotrust 350, 100% recycled
Dimensions	ISO 3018	48x48/96x96cm/Figura
Dimensional stability	EN 986	<0,2%
Total thickness	ISO 1765	Apr 7,0 mm. 0.28"
Surface pile thickness	ISO 1766	Apr 2,5 mm.
Tufts	ISO 1763	Apr 160.000 pr.m2
Total carpet weight	ISO 8543	Apr 2.600 g/m2 76.7 oz./yd2
Pile yarn weight	eTL	675 g/m2 19.9 oz./yd2
Surface pile density	ISO 8543.	Apr 0,140 g/cm3

### Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	ISO 6356	Antistatic
Acou.insu. from impact noise	eTL	25 dB
Acoustical absorption	eTL	0,25 aW
Suitability underfloorheating	eTL	Apr 0,12 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
	AATCC 16	4.0
Colour fastness to rubbing wet	ISO 105-X12	>3
	AATCC 165	5.0
Colour fastness to rubbing dry	ISO 105-X12	>3-4
	AATCC 165	5.0
Colourfast. to water patterned	ISO 105-E01	>4
Cleaning	AATCC 138	4.0
Colour fast.Oxides of nitrogen	AATCC 164	4.0
Other performance tests	ASTM D5252 Hexapod	4.0/3.5
	AATCC 134 Electrostatic propensity	1.7 kV

### Safety & Environment

Fire classification	MK GODKENDELSE	Approved
	VKF/AEAI	Approved
	ASTM E-648	Class 1
	ASTM E662 Smoke Density	<450
	ASTM D2859 Surface Flamm.	Pass

Product description	Methods	Product data	
CE Labeling	EN 13501-1 Euroclass	Cfl-s1	
	EN 14041	Certified	
	CPR	1021-CPR-010-2/16	
	Declaration of Performance	DOP 5C-PA-ECT350	
	Notified body no.	1021	
	Ce Year	12	
	Content of PCP EN 12673	DL	
	Formaldehyde emission	NA	
	Slip resistance EN 13893	Class DS	
	Indoor climate	DIM certificate	No. 006
		M1	With ECTA Backing
		BASTA	Registered
		Green Label Plus	Approved
		Emissions dans l'air intérieur	A+/A+
GECA		Approved	
Indoor Air Comfort Gold		Group 3	
ABG		ABG-28-01-03-03-2018	
Environment		Byggvarudeklaration	With ECTA Backing
		BREEAM-NOR	With ECTA Backing
	Environmental Product Decl.	EPD-EGE-20150220-CBC1-EN	
	Cradle To Cradle Certified	Bronze certified	
	Recycled Content, ISO 14021	Apr 18,0 %	
	Recycled Content for LEED	Apr 18,0 %	
	LEED	Qualified	

## Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Installation tiles	Direction of installation	Quarter turn/ monolithic
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

## Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK



THE URGE TO EXPLORE SPACE