

















Technical specifications




tessera® contour

Contour carpet tiles meet the requirements of EN 1307

Description		Tufted multi-height cut and loop pile carpet tile
	Dimensions	50cm x 50cm
	Total thickness	6.3mm ± 10%
	Pile height	3.5mm ± 0.5mm
	Collection size	13 colourways, 4m ² per box
	Application	EN 1307 Class 33, Suitable for any type of heavy contract application
	Pile composition	Refresh™ by Universal Fibers™. 100% polyamide 6.6
	Dye method	100% solution dyed
	Stitch density	254,880 per m ² ± 10%
	Pile weight	580 gsm ± 10%
	Total weight	4,095 gsm ± 10%
	Primary backing	Polyester
	Secondary backing	ProBac recycled mineral filler with low amount of modified bitumen, and polyester fleece. Contains over 76% recycled content.
	Castor chair use	BS EN 985 Minimum R value: ≥2.4
	Light fastness	BS EN ISO 105 B02 ≥ 5
	Dimensional stability	BS EN 986 ≤ 0.2%
	Impact sound reduction	ISO 10140-3 ΔL _w = 23 dB
	Creating Better Environments	
	Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources
	Recycled Content	Contour carpet tiles contain 68% recycled content by weight
	Indoor Air Quality	Contour meets 01350 Indoor Air Quality standard
	Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor
	Ska	Contour meets Ska Rating criteria for M12 soft floor coverings in office, retail and higher education schemes
	Guarantee	Contour carpet tiles are guaranteed for 10 years under general contract conditions provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.
	Installation method	Monolithic, quarter turn, tessellated, half drop or non-directional

Contour carpet tiles meet the requirements of EN 14041

CE
EN 14041

	Reaction to fire	EN 13501-1	B _{f1} -s1
	Slip resistance	EN 13893	DS: ≥0.30
	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

BREEAM ratings

Tessera Contour – Carpet Tiles (EN1307)

Building Type	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
Office	A+	A+	A	A	A+	✓

Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Contour carpet tiles are manufactured in a facility certified to SA8000® and OHSAS 18001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.

SAMPLE SERVICE
0800 731 2369
samples.uk@forbo.com

MADE IN THE UK

bimstore.co.uk

www.forbo-flooring.co.uk

creating better environments

forbo

FLOORING SYSTEMS