
MID CENTURY WEAVE CARPET TILES

HEMINGWAYDESIGN





Technical specifications

Forbo tufted carpet tiles meet the requirements of EN1307

	Description		Tufted multi-pile height loop carpet tile
	Dimensions		50cm x 50cm (Other sizes available for special orders)
Ŷ	Total thickness		7.0mm ± 10%
	Pile height		3.9mm ± 0.5mm
	Collection size		3 colourways, 4m² per box
	Application	EN 1307	Class 33, Suitable for any type of heavy contract application
	Pile composition		100% ECONYL® regenerated polyamide 6
	Dye method		100% solution dyed
	Stitch density		212,760 per m ² ± 10%
	Pile weight		796 gsm ± 10%
	Total weight		4,311 gsm ± 10%
	Primary backing		70% Polyester 30% nylon
	Secondary backing		Modified bitumen and polyester fleece
	Castor chair use	BS EN 985	Minimum R value: ≥2.4
深	Light fastness	BS EN ISO 105 B02	≥5
K Z	Dimensional stability	BS EN 986	≤0.2%
	Creating Better Environments		
	Renewable Electricity		All Forbo tufted carpet tiles are manufactured using 100% electricity made from renewable sources
	Recycled Content Indoor Air Quality		Forbo tufted carpet tiles contain over 50% recycled content by weight
- P			Forbo tufted carpet tiles meet 01350 Indoor Air Quality standard
Podbo back to the floor regulary factor flooring	Back to the Floor		Installation off cuts can be collected and recycled via Back to the Floor
	Ska		Forbo tufted carpet tiles meet Ska Rating criteria for M12 soft floor coverings in both office and retail schemes
	Installation method		Tessellated or quarter turn
	Forbo tufted carpet tiles meet the requirements of EN 140		C € EN 14041
B _m ·s1	Reaction to fire	EN 13501-1	B _{f1} -s1
DS	Slip resistance	EN 13893	DS: ≥0.30
F	Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 9 Ω : Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

Our recommended adhesive for Forbo tufted carpet tiles is 542 Eurofix tack plus.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have a certified Quality Management System in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing operations have a certified Environmental Management System in accordance with ISO 14001.

Forbo tufted carpet tiles are manufactured in a facility certified to SA8000°.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental Product Declarations (EPD's) or local building rating schemes such as BREEAM.









Contact:

Email: info.flooring.uk@forbo.com www.forbo-flooring.co.uk

Samples:

Tel: 0800 731 2369

