

# D




DREADNOUGHT

from our  
ENTRANCE & TRANSITION AREA RANGE







# DREADNOUGHT

 **MADE IN THE UK. MADE TO LAST.**

## Specification

<b>PRODUCT</b>	Dreadnought Heavy Contract Entrance Area Carpet & Tiles
<b>FIBRE CONSTRUCTION</b>	90% Polypropylene, 10% Recycled Polyester
<b>WEIGHT</b>	1495gm metre <sup>2</sup> (Sheet), 3995gm metre <sup>2</sup> (Tile)
<b>THICKNESS</b>	11mm (Sheet), 11.5mm (Tile)
<b>ROLL WIDTH</b>	 2 metre. Ribbing runs diagonally down the length of the roll
<b>TILE SIZE</b>	 50cm x 50cm (Tiles are Bitumen backed)
<b>COLOUR FASTNESS</b>	Light (BS EN ISO 105:B02) 6 Wet Rubbing (BS EN ISO 105:B01) 4-5 Dry Rubbing (BS EN ISO 105:X12) 4-5
<b>FLAMMABILITY</b>	(BS6307) Methenamine Pill Test - Pass
<b>BS EN 13501</b>	Euroclass E <sub>fl</sub> (Sheet) Euroclass E <sub>fl</sub> (Tile)
<b>INSTALLATION</b>	 Before laying Dreadnought, tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels. Dreadnought tiles should be laid rotationally, alternating the direction of the tiles through 90°. For details of subfloor preparation and a full guide to installation visit: <a href="http://www.heckmondwike-fb.co.uk">www.heckmondwike-fb.co.uk</a>
<b>ADHESIVE GUIDE</b>	Sheet carpet should be fully adhered with F Ball's F3 or Bostik Laybond Carpet Adhesive. For tiles, use Tackifier F41 or Bostik Laybond Carpet Tile Tackifier.
<b>MAINTENANCE</b>	To achieve maximum life expectancy, it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: <a href="http://www.heckmondwike-fb.co.uk">www.heckmondwike-fb.co.uk</a>

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may, therefore, show variations to the sample card. Heckmondwike reserves the right to change or modify product specifications without giving prior notice.

 EN 14041 Heckmondwike FB Liversedge WF15 7FH 15 Dreadnought Fibre Bonded Sheet Floorcovering intended for internal use  	 EN 14041 Heckmondwike FB Liversedge WF15 7FH 13 Dreadnought Tile Fibre Bonded Tile Floorcovering intended for internal use  
---	---



**BCFA**