


**Installation Method**



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Broome Street    **Color** 106211 Brick Glass    **Collection** NY+LON Streets    **Backing** GlasBac®

**Product Specifications**

Product Number	1417302500
Product Construction	Tufted Pattern Loop
Yarn System	Post-Consumer Content Nylon
Yarn Manufacturer	Universal
Dye Method	100% Solution Dyed
Soil/Stain Protection	<a href="#">Protekt2®</a>
Preservative Protection	Intersept®

	<b>Imperial</b>	<b>Metric</b>
Tufted Yarn Weight	28 oz/yd <sup>2</sup>	949 g/m <sup>2</sup>
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.16 in	4.1 mm
Pile Thickness	0.092 in	2.3 mm
Stitches	9 /in	35.4 ends/10cm
Pile Density	10,957 oz/yd <sup>3</sup>	406,283 g/m <sup>3</sup>
Size	19.69 in x 19.69 in	50cm x 50cm

**Performance Specifications**

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.7 to 1.9
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

**Health + Environmental Specifications**

<b>Carbon Footprint</b>	
Embodied Carbon (Cradle to Gate)	6.58 Kg CO <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	65%
Recycled Content (Pre Consumer)	64%
Recycled Content (Post Consumer)	2%
Indoor Air Quality	<a href="#">Green Label Plus #GLP0820</a> CDPH 01350
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	<a href="#">Green Circle Certified Environmental Facts NSF/ANSI 140 Gold</a>
End of Life	Carpet to Carpet Recycling through ReEntry®

**Technical Information**

Installation	<a href="#">Interface Installation Guidelines</a>
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>
Standard Backing	GlasBac®
Backing Options ( <a href="#">Learn more</a> )	CQuest™Bio, CQuest™GB, CushionBac Renew™, GlasBac®, GlasBac®RE, ReadyBac™
Tile Size Options	50cm x 50cm

