




Installation Method



Monolithic Non Directional

Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Duet **Colour** 303400 Parchment

Product Specifications

Product Number	1167
Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon contains recycled content
Standard Backing	Graphlex®
Optional Backing(s)	ReCushion Bac®, SONE®, CircuitBac Green
Size – Packaging	50 x 50 cm – 4 m² Box
Pile Yarn Weight	610 g/m² ± 5%
Total Weight	4099 g/m² ± 5%
Pile Height	3.4 mm +15% / - 10%
Total Thickness	6.6 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/10 - 39.4
Tufts per m²	200,940/m² ±5%

Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)					
Light Fastness	≥6 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	54.4				22.4	
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL _w EN ISO 10140-3	26 dB					
Rating of Sound Absorption (α _w) EN ISO 11654	0.15					
Sound Absorption (α _s) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.00	0.03	0.07	0.21	0.30	0.38

Environmental Specifications

Total Recycled Content	48.08%
Pre-Consumer (Total)	46.6%
Post-Consumer (Total)	1.48%
Yarn Recycled Content	52.5%
Pre-Consumer (Yarn)	42.5%
Post-Consumer (Yarn)	10%

Indoor Air Quality	GUT Prodis ID 3250B94C
	M1 Emission Certification - 2
	GLP 9819
	Danish Indoor Climate
	French A+

Potential Green Building Contribution

BREEAM (UK/International)		View potential BREEAM contribution			
BRE Green Guide Ratings					
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)
A	A	A+	A+	A+	A
LEED (US/International)		View Potential Leed Contribution			
HQE (France)		View Potential HQE Contribution			
DGNB (Germany)		View Potential DGNB Contribution			
Environmental Product Declaration		wc_eu-epd-int-20180117-duet-cbc1-en			

Carbon Footprint

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	9.55 kg CO ₂ eq./m ²
Delivery and Installation	0.67 kg CO ₂ eq./m ²
Use (10 Years)	3.43 kg CO ₂ eq./m ²
End of Life (Waste to Energy)	4.97 kg CO ₂ eq./m ²
Total (10 Years Lifetime)	18.62 kg CO ₂ eq./m ²
Carbon Neutral Floors™	Standard

Installation Impacts

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:
	Monolithic – 3-4%
	Non-directional – 1-2%
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

End of Life Options

ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

Technical Information

Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	15 years
Manufacturing Location	ISO 9001 & 14001 Certified Facilities in Europe

Performance Qualifications



Certifications

