




## Installation Method



Quarter Turn    Monolithic

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Collection** Employ    **Product** Employ Loop    **Colour** 4197001 Raffia

## Product Specifications

Product Number	4197
Product Construction	Tufted Level Loop Pile
Yarn System	100% Solution Dyed Nylon
Standard Backing	Graphlex®
Optional Backing(s)	ReCushion Bac®, SONE®
Size – Packaging	50 x 50 cm – 5 m² Box
Pile Yarn Weight	518 g/m² ± 5%
Effective Pile Yarn Weight	335 g/m² ± 10%
Total Weight	3934 g/m² ± 5%
Pile Height	2.6 mm +15% / - 10%
Total Thickness	5.7 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/10 - 39.4
Tufts per m²	200,940/m² ± 5%

## Performance Specifications

Wear Classification	EN 1307 33 Heavy Contract					
UPEC Classification	U3 P3 E1 C0					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	52.27			20.39		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	24 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.15					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.02	0.02	0.06	0.13	0.28	0.32

## Environmental Specifications

Total Recycled Content	46.8%
Pre-Consumer (Total)	46.8%
Post-Consumer (Total)	0%
Yarn Recycled Content	0%
Pre-Consumer (Yarn)	0%
Post-Consumer (Yarn)	0%

Indoor Air Quality	GUT Prodis ID 085C3EBF
	<a href="#">M1 Emission Certification - 1</a>
	<a href="#">GLP 9819</a>
	<a href="#">Danish Indoor Climate</a>
	French A+

## Potential Green Building Contribution

BREEAM (UK/International)		<a href="#">View potential BREEAM contribution</a>			
BRE Green Guide Ratings					
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
LEED (US/International)		<a href="#">View Potential Leed Contribution</a>			
HQE (France)		<a href="#">View Potential HQE Contribution</a>			
DGNB (Germany)		<a href="#">View Potential DGNB Contribution</a>			
Environmental Product Declaration		<a href="#">wc_eu-epd-int-20180115-employloop-cbc1-en</a>			

**Carbon Footprint**

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	7.92 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	0.64 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	3.24 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	5.66 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	17.46 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard

**Installation Impacts**

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:
	Quarter turn – 3-4%
	Monolithic – 3-4%
	For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

**End of Life Options**

Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

**Technical Information**

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a>

**Performance Qualifications**



**Certifications**

