



**Product** Glazing **Colour** 9079002 Desert Shadow

**Installation Method**



Ashlar Herringbone

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product Specifications**

Product Number	9079
Product Construction	Tufted Patterned Structured Loop Pile
Yarn System	100% Solution Dyed Nylon contains recycled content
Standard Backing	Graphlex®
Optional Backing(s)	ReCushion Bac®
Size – Packaging	25 x 100 cm – 5 m² Box
Pile Yarn Weight	644 g/m² ± 5%
Total Weight	4088 g/m² ± 5%
Pile Height	3.9 mm +15% / - 10%
Total Thickness	6.7 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/12 - 47.2
Tufts per m²	184,080/m² ±5%

**Performance Specifications**

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Bfl-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	33.4			7.7		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	26 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.02	0.03	0.08	0.19	0.32	0.40

**Environmental Specifications**

Total Recycled Content	60.8%					
Pre-Consumer (Total)	59%					
Post-Consumer (Total)	1.8%					
Yarn Recycled Content	75%					
Pre-Consumer (Yarn)	65%					
Post-Consumer (Yarn)	10%					
Indoor Air Quality	GUT Prodis ID DDB7B170 <a href="#">M1 Emission Certification - 2</a> French A+ <a href="#">Danish Indoor Climate</a> <a href="#">GLP 9819</a> <a href="#">GUI Standard</a>					
Potential Green Building Contribution						
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>					
BRE Green Guide Ratings						
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)	
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available	
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>					
HQE (France)	<a href="#">View Potential HQE Contribution</a>					
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>					
Environmental Product Declaration	<a href="#">wc_eu-epd-int-20170101-glazing-cbc1-en</a>					

**Carbon Footprint**

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	7.08 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	0.86 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	3.32 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	5.11 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	16.37 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard

**Installation Impacts**

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Ashlar – 3-5 %  Herringbone – 3-5%  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

**End of Life Options**

Waste to Energy	Can be incinerated in appropriate waste to energy plant.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.

**Technical Information**

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a>

**Performance Qualifications**



**Certifications**

