



Installation Method



Monolithic

Quarter Turn

Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Heuga 493 **Colour** 009305 Basalt

Product Specifications

Product Number	1261
Product Construction	Tufted Plain Level Loop Pile
Yarn System	100% Polypropylene
Standard Backing	Graphlar®
Size – Packaging	50 x 50 cm – 5 m² Box
Pile Yarn Weight	545 g/m² ± 5%
Total Weight	3840 g/m² ± 5%
Pile Height	2.8 mm +15% / - 10%
Total Thickness	6 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/10 - 39.4
Tufts per m²	168,100/m² ±5%

Performance Specifications

Wear Classification	EN 1307 31 Moderate Contract					
Castor Chair Rating	≥2.0 (EN 985) Occasional Use					
Flammability	(EN ISO 9239-1) Euroclass Dfl-s1 (EN 13501-1)					
Light Fastness	≥5 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	33.8			7.9		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL _w EN ISO 10140-3	23 dB					
Rating of Sound Absorption (α _w) EN ISO 11654	0.20					
Sound Absorption (α _s) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.01	0.02	0.06	0.14	0.19	0.21

Environmental Specifications

Total Recycled Content	59.23%
Pre-Consumer (Total)	59.23%
Post-Consumer (Total)	0%
Yarn Recycled Content	0%
Pre-Consumer (Yarn)	0%
Post-Consumer (Yarn)	0%
Indoor Air Quality	GUT Prodis ID FE8CD351 French A+ Danish Indoor Climate Compliant with LEED EQ 4.3 credit GUI Standard
Potential Green Building Contribution	
BREEAM (UK/International)	View potential BREEAM contribution
LEED (US/International)	View Potential Leed Contribution
HQE (France)	View Potential HQE Contribution
DGNB (Germany)	View Potential DGNB Contribution
Environmental Product Declaration	EPD-IFF-2011411-E

Carbon Footprint	
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Cradle-To-Gate (Raw Materials and Production)	4.8 kg CO ₂ eq./m ²
Carbon Neutral Floors™	Standard
Installation Impacts	
Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below: Quarter turn – 3-4% Monolithic – 3-4% For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
End of Life Options	
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Technical Information	
Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	7 years
Manufacturing Location	ISO 9001, 14001 & 45001 Certified Facilities in Europe

Performance Qualifications



Certifications

