



Collection Near & Far Product NF401 Colour 7959003 Shale

**Installation Method**



Ashlar Herringbone

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product Specifications**

Product Number	7959
Product Construction	Tapestry Tufted Patterned Structured Tip Sheared Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex®
Optional Backing(s)	ReCushion Bac®
Size – Packaging	25cm x 100cm 4.5m2 Box
Pile Yarn Weight	1153 g/m <sup>2</sup> ± 5%
Total Weight	4636 g/m <sup>2</sup> ± 5%
Pile Height	6.6 mm +15% / - 10%
Total Thickness	11 mm ± 0.5 mm
Gauge – Ends per 10 cm	1/10 - 39.4
Tufts per m <sup>2</sup>	116,230/m <sup>2</sup> ±5%

**Performance Specifications**

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cf1-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	31.6			6.9		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	29 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.20					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.01	0.04	0.12	0.27	0.41	0.53

**Environmental Specifications**

Total Recycled Content	60.24%
Pre-Consumer (Total)	47.88%
Post-Consumer (Total)	12.36%
Yarn Recycled Content	100%
Pre-Consumer (Yarn)	50%
Post-Consumer (Yarn)	50%

Indoor Air Quality  
 GUT Prodis ID D03BE29D  
[M1 Emission Certification - 3](#)  
 French A+  
[Danish Indoor Climate](#)  
[GLP 9819](#)  
[GUI Standard](#)

**Potential Green Building Contribution**

BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>				
BRE Green Guide Ratings					
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)
A+	A	A+	A+	A+	A+
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>				
HQE (France)	<a href="#">View Potential HQE Contribution</a>				
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>				
Environmental Product Declaration	<a href="#">wc_eu-epd-int-20180094-nf401-cbc1-en</a>				

**Carbon Footprint**

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	6.71 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	0.69 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	3.21 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	7.35 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	22.14 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard

**Installation Impacts**

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Ashlar – 3-5 %  Herringbone – 3-5%  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

**End of Life Options**

Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.

**Technical Information**

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a>

**Performance Qualifications**



**Certifications**

