Interface®



Installation Method

>	^	>	^	^	^	^	^
^	>	^	>	^	^	^	^
>	^	>	^	^	^	^	^
^	>	^	>	^	^	^	^

Quarter Turn Monolithi

Interface European Manufacturing BV reserve the right to change or modify specifications.

Product Series.1 Textured Colour 4202001 Metal

Product Specifications							
Product Number	4202						
Product Construction	Tufted Pat	terned Struc	tured Loop Pi	ile			
Yarn System	100% Solution Dyed N		ylon				
Standard Backing	Graphlex [®]						
Size – Packaging	50 x 50 cm – 5 m² Box						
Pile Yarn Weight	$440 \text{ g/m}^2 \pm 5\%$						
Total Weight	3834 g/m² ± 5%						
Pile Height	3 mm +15% / - 10%						
Total Thickness	6 mm ± 0.5 mm						
Gauge – Ends per 10 cm	1/12 - 47.2						
Tufts per m²	217,120/m² ±5%						
Performance Specifications							
Wear Classification	EN 1307 33 Heavy Contract						
Castor Chair Rating	≥2.4 (EN 985) Continuous Use						
E1 139	(EN ISO 9239-1) Euroclass Cfl-s1 (EN 13501-1)						
Flammability	Bfl-s1 on request						
Light Fastness	≥7 (ISO 105-B02)						
	LRV – L value LRV – Y value						
Light Reflectance Value (LRV)	49.73	49.73			18.19		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)						
Impact Sound Insulation ΔL _w EN ISO 10140-3	23 dB						
Rating of Sound Absorption (α_w) EN ISO 11654	0.20						
Sound Absorption (α _s)	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	
EN ISO 354	0.01	0.03	0.09	0.24	0.32	0.42	

Environmental Specifications

Total Recycled Content			49.2%				
Pre-Consumer (Total)			49.2%				
Post-Consumer	Total)	0%					
Yarn Recycled Conf	ent	0%					
Pre-Consumer (Yarn)			0%				
Post-Consumer	Yarn)	0%	0%				
Indoor Air Quality		GUT Pro	GUT Prodis ID EFE76FAC				
		Danish I	ndoor Climate				
		French A	French A+				
		M1 Emis	M1 Emission Certification - 1				
		GLP 981	<u>GLP 9819</u>				
		GUI Star	GUI Standard				
Potential Green Buil	ding Contribution						
BREEAM (UK/In	ternational)	View pot	tential BREEAM contrib	oution			
BRE Green Guid	e Ratings						
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)		
Not Available	Not Available	Not Available	Not Available	Not Available	Not Available		
LEED (US/Intern	ational)	View Pot	tential Leed Contribution	<u>n</u>			
HQE (France)		View Pot	View Potential HQE Contribution				
DGNB (Germany	')	View Pot	View Potential DGNB Contribution				
Environmental P	oduct Declaration	wc_eu-e	pd-int-20180115-series	1textured-cbc1-en			

Page 1 of 2 18 March 2019



Carbon Footprint	
Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	7.18 kg CO ₂ eq./m ²
Delivery and Installation	0.61 kg CO ₂ eq./m ²
Use (10 Years)	3.24 kg CO ₂ eq./m ²
End of Life (Waste to Energy)	5.49 kg CO ₂ eq./m ²
Total (10 Years Lifetime)	16.51 kg CO ₂ eq./m ²
Carbon Neutral Floors™	Standard
Installation Impacts	
Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:
	Monolithic – 3-4%
	Quarter turn – 3-4%
	For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles [®]	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs
End of Life Options	
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Waste to Energy	Can be incinerated in appropriate waste to energy plant.
Technical Information	
Installation	See recommended Interface installation guidelines
Maintenance	See recommended Interface maintenance guidelines
Warranty	15 years
Manufacturing Location	ISO 9001 & 14001 Certified Facilities in Europe

Performance Qualifications



Certifications











Page 2 of 2 18 March 2019