


**Installation Method**



Ashlar Brick

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).

**Product** Step it Up **Color** 106332 Citrine **Collection** Look Both Ways **Backing** GlasBac®

**Product Specifications**

Product Number	1473802500	
Product Construction	Tufted Textured Loop	
Yarn System	Post-Consumer Content Nylon	
Yarn Manufacturer	Universal	
Dye Method	100% Solution Dyed	
Soil/Stain Protection	Protekt®	
Preservative Protection	Intersept®	
	<b>Imperial</b>	<b>Metric</b>
Tufted Yarn Weight	18 oz/yd²	610 g/m²
Machine Gauge	1/12 in	39.4 ends/10cm
Pile Height	0.14 in	3.6 mm
Pile Thickness	0.084 in	2.1 mm
Stitches	10.8 /in	42.5 ends/10cm
Pile Density	7,714 oz/yd³	286,033.4 g/m³
Size	19.69 in x 19.69 in	50cm x 50cm

**Performance Specifications**

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Traffic Classification	Heavy
Fiber Modification Ratio	1.7 to 1.9
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

**Health + Environmental Specifications**

Carbon Footprint	6.58 Kg CO <sub>2</sub> /M <sup>2</sup>
Carbon Offsets	Carbon Neutral Floors™
Total Recycled Content	72%
Recycled Content (Post Industrial)	71%
Recycled Content (Post Consumer)	1%
Indoor Air Quality	<a href="#">Green Label Plus #GLP0820</a> CDPH 01350
Material Composition	Free of Added Formaldehyde, Heavy Metals and Ortho Phthalates, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	<a href="#">Environmental Product Declaration</a>
Disclosure of Product Ingredients	<a href="#">Health Product Declaration</a>
Environmental Certifications	<a href="#">Green Circle Certified Environmental Facts NSF/ANSI 140 Gold</a>
LEED v4	Contributes to multiple IEQ and MR credits

**Technical Information**

Installation	<a href="#">Interface Installation Guidelines</a>
Maintenance	<a href="#">Recommended Interface Maintenance Guidelines</a>
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	<a href="#">15 Year Standard Carpet Warranty</a>
Standard Backing	GlasBac®
Backing Options ( <a href="#">Learn more</a> )	CushionBac Renew™, GlasBac®, GlasBac®RE, ReadyBac™
Tile Size Options	50cm x 50cm
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified facilities in Troup County, Georgia, United States</a>

