




Installation Method



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Step this Way **Color** 106325 Ebony **Collection** Look Both Ways **Backing** GlasBac®

Product Specifications

Product Number	1417602500	
Product Construction	Tufted Sheared	
Yarn System	Post-Consumer Content Nylon	
Yarn Manufacturer	Universal	
Dye Method	100% Solution Dyed	
Soil/Stain Protection	Protekt2®	
Preservative Protection	Intersept®	
	Imperial	Metric
Tufted Yarn Weight	24 oz/yd ²	814 g/m ²
Machine Gauge	1/10 in	39.4 ends/10cm
Pile Height	0.14 in	3.6 mm
Pile Thickness	0.082 in	2.1 mm
Stitches	10 /in	39.4 ends/10cm
Pile Density	10,537 oz/yd ³	390,709.6 g/m ³
Size	19.69 in x 19.69 in	50cm x 50cm

Performance Specifications

Flooring Radiant Panel	(ASTM E-648) Passes
Smoke Density	(ASTM E 662) ≤ 450
Flammability	Passes Methenamine Pill Test (DOC-FF1-70)
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static	(AATCC - 134) < 3.0 KV
Dimensional Stability	AACHEN Din 54318 <.10%
Traffic Classification	Moderate
Fiber Modification Ratio	1.7 to 1.9
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition

Health + Environmental Specifications

Carbon Footprint	6.58 Kg CO ₂ /M ²
Carbon Offsets	Carbon Neutral Floors™
Total Recycled Content	72%
Recycled Content (Post Industrial)	71%
Recycled Content (Post Consumer)	1%
Indoor Air Quality	Green Label Plus #GLP0820 CDPH 01350
Material Composition	Free of Added Formaldehyde, Heavy Metals and Ortho Phthalates, Fluorinated Chemicals (PFAS), and Halogenated Flame Retardants.
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration
Environmental Certifications	Green Circle Certified Environmental Facts NSF/ANSI 140 Gold
LEED v4	Contributes to multiple IEQ and MR credits

Technical Information

Installation	Interface Installation Guidelines
Maintenance	Recommended Interface Maintenance Guidelines
Reclamation	View details on our ReEntry™ Program
Warranty	15 Year Standard Carpet Warranty
Standard Backing	GlasBac®
Backing Options (Learn more)	CushionBac Renew™, GlasBac®, GlasBac®RE, ReadyBac™
Tile Size Options	50cm x 50cm
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States

