




**Installation Method**



Herringbone Ashlar

Interface European Manufacturing BV reserve the right to change or modify specifications.

**Product** Touch of Timber **Colour** 4191005 Silver Birch

**Product Specifications**

Product Number	4191
Product Construction	Microtuft Patterned Level Loop Pile
Yarn System	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex®
Size – Packaging	25 x 100 cm – 5 m² Box
Pile Yarn Weight	499 g/m² ± 5%
Total Weight	4239 g/m² ± 5%
Total Thickness	5.1 mm ± 0.5 mm
Gauge – Ends per 10 cm	5/64 - 50.4
Tufts per m²	186,480/m² ±5%

**Performance Specifications**

Wear Classification	EN 1307 33 Heavy Contract					
Castor Chair Rating	≥2.4 (EN 985) Continuous Use					
Flammability	(EN ISO 9239-1) Euroclass Cf-s1 (EN 13501-1)					
Light Fastness	≥7 (ISO 105-B02)					
Light Reflectance Value (LRV)	LRV – L value			LRV – Y value		
	53.1			21.1		
Dimensional Stability	≤0.2% (ISO 2551/EN 986)					
Impact Sound Insulation ΔL <sub>w</sub> EN ISO 10140-3	14 dB					
Rating of Sound Absorption (α <sub>w</sub> ) EN ISO 11654	0.15					
Sound Absorption (α <sub>s</sub> ) EN ISO 354	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz
	0.01	0.00	0.06	0.17	0.32	0.30

**Environmental Specifications**

Total Recycled Content	69.83%					
Pre-Consumer (Total)	64.15%					
Post-Consumer (Total)	5.68%					
Yarn Recycled Content	100%					
Pre-Consumer (Yarn)	50%					
Post-Consumer (Yarn)	50%					
Indoor Air Quality	GUT Prodis ID BCCD7633 <a href="#">M1 Emission Certification - 2</a> French A+ <a href="#">Danish Indoor Climate</a> <a href="#">GLP 9324</a>					
Potential Green Building Contribution						
BREEAM (UK/International)	<a href="#">View potential BREEAM contribution</a>					
BRE Green Guide Ratings						
Commercial	Domestic	Education	Health	Retail (Fashion)	Retail (Durability)	
A+	A+	A+	A+	A+	A+	
LEED (US/International)	<a href="#">View Potential Leed Contribution</a>					
HQE (France)	<a href="#">View Potential HQE Contribution</a>					
DGNB (Germany)	<a href="#">View Potential DGNB Contribution</a>					
Environmental Product Declaration	<a href="#">Touch of Timber EPD-INT-20170100-CBC1-EN</a>					

Carbon Footprint

Full Life Cycle Carbon Footprint	According to EPD or EPD calculation method
Raw Materials and Production	3.86 kg CO <sub>2</sub> eq./m <sup>2</sup>
Delivery and Installation	0.75 kg CO <sub>2</sub> eq./m <sup>2</sup>
Use (10 Years)	3.32 kg CO <sub>2</sub> eq./m <sup>2</sup>
End of Life (Waste to Energy)	4.52 kg CO <sub>2</sub> eq./m <sup>2</sup>
Total (10 Years Lifetime)	12.44 kg CO <sub>2</sub> eq./m <sup>2</sup>
Carbon Neutral Floors™	Standard

Installation Impacts

Installation Waste	In a typical installation (rectangular building, installed before walls) using the installation method below:  Herringbone 3-5%  Ashlar – 3-5 %  For reference: 2 m wide broadloom typically generates 7-10% installation waste
TacTiles®	Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs

End of Life Options

Waste to Energy	Can be incinerated in appropriate waste to energy plant.
ReUse	Can be cleaned and reused in a non-critical location to extend its useful life.
Recycling	Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles.

Technical Information

Installation	<a href="#">See recommended Interface installation guidelines</a>
Maintenance	<a href="#">See recommended Interface maintenance guidelines</a>
Warranty	15 years
Manufacturing Location	<a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a>

Performance Qualifications



Certifications

