



### Installation Method



Monolithic

Interface European Manufacturing BV reserve the right to change or modify specifications.

Collection Urban Retreat Product UR303 Colour 326995 Stone

### Product Specifications

|                        |  |
|------------------------|--|
| Product Number         | 7132   |
| Product Construction   | Tufted Patterned Structured Tip Sheared Pile |
| Yarn System            | 100% Recycled Solution Dyed Nylon            |
| Standard Backing       | Graphlex®                                    |
| Optional Backing(s)    | ReCushion Bac®                               |
| Size – Packaging       | 50 x 50 cm – 4 m² Box                        |
| Pile Yarn Weight       | 783 g/m² ± 5%                                |
| Total Weight           | 4494 g/m² ± 5%                               |
| Pile Height            | 3.1 mm +15% / - 10%                          |
| Total Thickness        | 7.2 mm ± 0.5 mm                              |
| Gauge – Ends per 10 cm | 1/10 - 39.4                                  |
| Tufts per m²           | 165,480/m² ±5%                               |

### Performance Specifications

|  |   |        |        |               |         |         |
|--|---|--------|--------|---------------|---------|---------|
| Wear Classification  | EN 1307 33 Heavy Contract                     |        |        |               |         |         |
| Castor Chair Rating  | ≥2.4 (EN 985) Continuous Use                  |        |        |               |         |         |
| Flammability   | (EN ISO 9239-1) Euroclass Cf1-s1 (EN 13501-1) |        |        |               |         |         |
| Light Fastness   | ≥7 (ISO 105-B02)                              |        |        |               |         |         |
| Light Reflectance Value (LRV)                                | LRV – L value                                 |        |        | LRV – Y value |         |         |
|  | 33.2  |        |        | 7.6           |         |         |
| Dimensional Stability  | ≤0.2% (ISO 2551/EN 986)                       |        |        |               |         |         |
| Impact Sound Insulation ΔL <sub>w</sub><br>EN ISO 10140-3    | 24 dB   |        |        |               |         |         |
| Rating of Sound Absorption (α <sub>w</sub> ) EN<br>ISO 11654 | 0.20  |        |        |               |         |         |
| Sound Absorption (α <sub>s</sub> )<br>EN ISO 354             | 125 Hz  | 250 Hz | 500 Hz | 1000 Hz       | 2000 Hz | 4000 Hz |
|  | 0.02  | 0.04   | 0.07   | 0.27          | 0.33    | 0.48    |

### Environmental Specifications

|                        |        |
|------------------------|--------|
| Total Recycled Content | 60.94% |
| Pre-Consumer (Total)   | 52.28% |
| Post-Consumer (Total)  | 8.67%  |
| Yarn Recycled Content  | 100%   |
| Pre-Consumer (Yarn)    | 50%    |
| Post-Consumer (Yarn)   | 50%    |

|                    |   |
|--------------------|---|
| Indoor Air Quality | GUT Prodis ID 9F6CFA50                        |
|                    | <a href="#">M1 Emission Certification - 2</a> |
|                    | French A+                                     |
|                    | <a href="#">Danish Indoor Climate</a>         |
|                    | <a href="#">GLP 9819</a>                      |
|                    | <a href="#">GUI Standard</a>                  |

### Potential Green Building Contribution

|                                   |          |  |        |                  |                     |
|-----------------------------------|----------|--|--------|------------------|---------------------|
| BREEAM (UK/International)         |          | <a href="#">View potential BREEAM contribution</a>   |        |                  |                     |
| BRE Green Guide Ratings           |          |  |        |                  |                     |
| Commercial                        | Domestic | Education  | Health | Retail (Fashion) | Retail (Durability) |
| A+                                | A        | A+   | A+     | A+               | A+                  |
| LEED (US/International)           |          | <a href="#">View Potential Leed Contribution</a>     |        |                  |                     |
| HQE (France)                      |          | <a href="#">View Potential HQE Contribution</a>      |        |                  |                     |
| DGNB (Germany)                    |          | <a href="#">View Potential DGNB Contribution</a>     |        |                  |                     |
| Environmental Product Declaration |          | <a href="#">wc_eu-epd-int-20180094-ur303-cbc1-en</a> |        |                  |                     |

**Carbon Footprint**

|                                  |   |
|----------------------------------|---|
| Full Life Cycle Carbon Footprint | According to EPD or EPD calculation method  |
| Raw Materials and Production     | 5.45 kg CO <sub>2</sub> eq./m <sup>2</sup>  |
| Delivery and Installation        | 0.61 kg CO <sub>2</sub> eq./m <sup>2</sup>  |
| Use (10 Years)                   | 3.21 kg CO <sub>2</sub> eq./m <sup>2</sup>  |
| End of Life (Waste to Energy)    | 6.51 kg CO <sub>2</sub> eq./m <sup>2</sup>  |
| Total (10 Years Lifetime)        | 15.78 kg CO <sub>2</sub> eq./m <sup>2</sup> |
| Carbon Neutral Floors™           | Standard                                    |

**Installation Impacts**

|                    |  |
|--------------------|--|
| Installation Waste | In a typical installation (rectangular building, installed before walls) using the installation method below:<br><br>Monolithic – 3-4%<br><br>For reference: 2 m wide broadloom typically generates 7-10% installation waste |
| TacTiles®          | Optimised for glue-free installation with TacTiles® connectors with virtually zero VOCs  |

**End of Life Options**

|                 |   |
|-----------------|---|
| ReUse           | Can be cleaned and reused in a non-critical location to extend its useful life.                         |
| Recycling       | Can be returned through the Interface ReEntry scheme and be reused as raw material in new carpet tiles. |
| Waste to Energy | Can be incinerated in appropriate waste to energy plant.  |

**Technical Information**

|                        |   |
|------------------------|---|
| Installation           | <a href="#">See recommended Interface installation guidelines</a>   |
| Maintenance            | <a href="#">See recommended Interface maintenance guidelines</a>    |
| Warranty               | 15 years  |
| Manufacturing Location | <a href="#">ISO 9001 &amp; 14001 Certified Facilities in Europe</a> |

**Performance Qualifications**



**Certifications**

