




#### Installation Methods



Ashlar Herringbone

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer)

**Collection** World Woven **Product** WW870 **Colour** 8111-006-000 Natural Weft

#### Product Specifications

|  |  |
|--|--|
| Product Number                                   | 8111   |
| Product Construction                             | Tufted Textured Loop                                 |
| Yarn / Fibre                                     | BCF Nylon Type 6 - 100% Recycled content             |
| Yarn Manufacturer                                | Aquafil  |
| Colour System                                    | 100% Solution Dyed                                   |
| Soil/Stain Protection                            | Protekt <sup>2®</sup>                                |
| Preservative Protection                          | Intersept <sup>®</sup>                               |
| Tufted Pile Weight                               | 23 oz/yd <sup>2</sup> ±10% 780 g/m <sup>2</sup> ±10% |
| Machine Gauge                                    | 12th Gauge   |
| Stitches   | 43/10cm 9.8/in                                       |
| Pile Thickness                                   | 3.0 mm ± 0.5mm                                       |
| Total Thickness                                  | 6.5 mm ± 0.5mm                                       |
| Pile Density                                     | 7,962 oz/yd <sup>3</sup> ± 10%                       |
| Size Description                                 | 25cm X 1m  |
| Backing Structure ( <a href="#">Learn more</a> ) | GlasBac <sup>®</sup>                                 |

#### Performance Specifications

|   |  |
|---|--|
| Area of Use                             | Commercial - Heavy Duty  |
| ACCS                                    | Commercial Extra Heavy Duty & Stairs                                       |
| Stability - Delaminating                | ASTM D3936 ≥ 2.5lbs/in<br>ISO2551 ≤ 0.1%<br>AS/NZS 2111.16 ≥ 50 Newtons    |
| Stability - Dimensional Stability       | ISO/PAS 17984 < 0.2%<br>ISO 2551 ≤ 0.1%<br>ISO 2551 ≤ 0.2%                 |
| Stability - Tuft Bind                   | AS/NZS 2111.15 >30 Newtons<br>ISO 4919 ≥ 30 Newtons<br>ASTM D1335 ≥ 8.0lbs |
| Wear - Castor Chair                     | BS-EN 985 r ≥ 2.4<br>ISO 4918 r ≥ 2.4                                      |
| Colour Fastness to Light                | AATCC 16E ≥ 4<br>AS2001 1.4.21 ≥ 4<br>ISO 105-B02 ≥ 4 - 5                  |
| Colour Fastness to Rubbing and Crocking | AATCC 165 ≥ 4<br>ISO 105-X12 ≥ 4-5<br>AS/NZS2111.19.1 ≥ 4                  |
| Colour Fastness to Water                | AATCC 107 ≥ 4<br>ISO105-E01 ≥ 4-5<br>AS2001.4.21 ≥ 4                       |
| Flammability - Radiant Panel            | ASTM E648 Class 1<br>ISO 9239-1 B1   |
| Flammability - Smoke density            | ASTM E662 Density ≤ 450<br>ISO 9239-1 Density < 750 %.min                  |
| Antistatic                              | AATCC 134 < 3000 Volts<br>BS ISO 6356 ≤ 2.0Kv                              |
| Antimicrobial Treatment                 | AATCC 171 Washed<br>ASTME-2471 Complete Inhibition                         |

| <b>Generic Tests</b>                |   |
|-------------------------------------|---|
| Acoustic - Nylon                    | Absorption Coefficient - NRC $\geq$ 0.10                                      |
| Dynamic Loading                     | AS/NZS 2111.2 < 12.5% loss<br>ISO 2094 $\geq$ 85%                             |
| Green Carpet (VOC)                  | ASTM D5116 Accredited<br>ISO 10580 Accredited                                 |
| Static Loading                      | AS/NZS2111.13 < 6% Loss<br>ISO 015/3415 Thickness after 60 mins recovery >85% |
| Thermal Resistance                  | ASTM C518 R Value $\geq$ 0.5  |
| <b>Environmental Specifications</b> |   |
| Recycled Content %                  | 55-70   |
| Other Environmental Claims          | <a href="#">View Environmental Accreditations</a>                             |
| Ingredients and Life Cycle Impacts  | <a href="#">View our Environmental Product Declarations</a>                   |
| End of Life                         | Carpet to Carpet Recycling  |
| Carbon Neutral Floors™              | Standard  |
| <b>Technical Information</b>        |   |
| Maintenance                         | <a href="#">View recommended Interface Maintenance guidelines online</a>      |
| Reclamation                         | <a href="#">View details on our ReEntry™ Program</a>                          |
| Warranty                            | 15 Year Standard Warranty   |