

CONSEQUENCE 2.0



Effect / Part Two / React / Sequel / Spin Off / Upshot

Construction	Tufted, Luxury Textured Loop Pile
Face Fibre	100% Nylon 6 including 40% ECONYL® made with 100% regenerated fibre
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	915 g/m ²
Gauge	47.2 / 10 cm
Rows	47.9 / 10 cm
Tuft Density	226,088 /m ²
Finished Pile Height	5.6 mm
Standard Backing	Comfort Plus® 90% Recycled Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	11.8 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4630 g/m ²
Tiles per Box	16 (4m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	33 dB
Sound Absorption (ISO354)	0.3 (H) Class D
Alpha s values	125Hz 0.03, 250Hz 0.07, 500Hz 0.42, 1000Hz 0.26, 2000Hz 0.36, 4000Hz 0.45

ENVIRONMENTAL

40% regenerated content yarn (20% post consumer)

90% Recycled content cushion backing 23% Recycled content by total product weight (9% post consumer)

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION

<p>Part Two/Sequel</p> <p>Monolithic</p>	<p>Effect/React</p> <p>Brick</p>	<p>Spin Off/Upshot</p> <p>Half Drop</p>
--	----------------------------------	---

CE MARKING

--	--	--	--	--	--