

JUXTAPOSE 2.0

Brights / Neutrals



Construction	Tufted, Level Loop Pile
Face Fibre	Universal® Fibres solution-dyed Type 6 6 Nylon
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	690 g/m ²
Gauge	40.5 / 10 cm
Rows	52 / 10 cm
Tuft Density	210,000 /m ²
Finished Pile Height	5.0 mm
Standard Backing	Comfort Plus® 90% Recycled Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	10.7 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4100 g/m ²
Tiles per Box	18 (4.5m ²)

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Bfl - s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	37 dB
Sound Absorption (ISO354)	0.35 Class D
Alpha s values	125Hz 0.00, 250Hz 0.09, 500Hz 0.52 1000Hz 0.27, 2000Hz 0.37, 4000Hz 0.42

ENVIRONMENTAL

18% Recycled content by total product weight

20% Recycled content yarn

90% Recycled content cushion backing

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

WARRANTIES

15 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

CERTIFICATIONS

INSTALLATION



CE MARKING

--	--	--	--	--	--	--