

# ARTISTIC LIBERTIES



Outspoken Tradition / Outspoken Tradition Inset / Historic Clashes / Historic Clashes Inset / Without Reserve

|                                |  |
|--------------------------------|--|
| <b>Construction</b>            | Tufted, Structured Loop Pile   |
| <b>Face Fibre</b>              | ECONYL® Type 6 nylon made with 100% regenerated nylon  |
| <b>Soil Release</b>            | StainSmart® for soil release, liquid repellence  |
| <b>Finished Face Weight</b>    | 490 g/m <sup>2</sup>   |
| <b>Gauge</b>                   | 47.2 / 10 cm   |
| <b>Rows</b>                    | 44 / 10 cm   |
| <b>Tuft Density</b>            | 224,000 /m <sup>2</sup>  |
| <b>Finished Pile Height</b>    | 2.5 mm   |
| <b>Standard Backing</b>        | Comfort Lite 90% Recycled content Polyurethane cushion Available with TractionBack® on request |
| <b>Nominal Total Thickness</b> | 8.3 mm   |
| <b>Tile Size</b>               | 50 cm x 50 cm  |
| <b>Nominal Total Weight</b>    | 3800 g/m <sup>2</sup>  |
| <b>Tiles per Box</b>           | 22 (5.5m <sup>2</sup> )  |

## PERFORMANCE

|   |   |
|---|---|
| <b>Flammability (Euroclassification EN13501:1-2002)</b> | Class Bfl - s1  |
| <b>Flammability (Radiant Panel ASTM-E-648)</b>          | Class 1   |
| <b>Flammability (Hot Metal Nut BS4790)</b>              | Low Radius of Char  |
| <b>Use Classification (EN 1307)</b>                     | Class 33 Heavy Commercial Use   |
| <b>Static Electricity (ISO 6356)</b>                    | Pass ≤ 2.0 KV Permanent Conductive Fibre                                  |
| <b>Impact Sound (ISO 10140-3)</b>                       | 31 dB   |
| <b>Sound Absorption (ISO354)</b>                        | 0.25 Class E  |
| <b>Alpha s values</b>                                   | 125Hz 0.01, 250Hz 0.07, 500Hz 0.59, 1000Hz 0.18, 2000Hz 0.26, 4000Hz 0.36 |

## ENVIRONMENTAL

100% regenerated content yarn

90% recycled Polyurethane cushion backing  
26% recycled content including up to 7% post consumer content

Manufactured in ISO14001 certified location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verified - BRE certified

## WARRANTIES

12 year wear warranty

Lifetime Antistatic guarantee

Latent Defects guarantee

## CERTIFICATIONS

|  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |
|  |  |  |  |  |  |  |  |  |  |

## INSTALLATION

Monolithic

## CE MARKING