

FREELAY LUXURY VINYL TILE

Eero / Fargesia Bamboo / Heritage Wood / Kokutan 5.0 / Polished Concrete 5.0 / PowerGrid 5.0



Construction	High Performance Luxury Vinyl Tile
Finish	Adámas™ UV-Cured Polyurethane
Wear Layer Thickness	0,7 mm
Overall Thickness	5 mm
Edge Profile	Micro Bevel
Product Weight	8800 g/m ²

PERFORMANCE

Critical Radiant Flux (ASTM E648-10)	Pass - Class 1
Flammability (EN 13501-1.2002)	Class Bfl-s1
Use Classification (EN 10852.2012)	Class 34 Very Heavy Commercial Use, Class 43 Heavy-Light Industrial Use
Castor Chair (ISO 4918: 2009)	Pass
Determination of Anti-slip (DIN 51130)	R10
Flexibility (ISO 242344)	Pass
Heat Stability by Colour Change (ASTM F1514-03)	Pass
Light Stability (ASTM F1515 - 03)	Pass
Static Electrical Propensity (ISO 6356)	Pass ≤2.0 KV
Dimensional Stability (EN ISO 23999)	Pass
Resistance to Chemicals (ASTM F925-13)	Pass
Static Load Limit (ASTM F970-07)	Pass

INSTALLATION

Freelay with perimeter glue

WARRANTIES

12 year wear warranty

TILE/PLANK SIZE

Eero	228.6 x 1516.9 mm (9" x 60")
Fargesia Bamboo	228.6 x 1516.9 mm (9" x 60")
Heritage Wood	228.6 x 1516.9 mm (9" x 60")
Kokutan 5.0	228.6 x 1516.9 mm (9" x 60")
Polished Concrete 5.0	457.2 x 914.4 mm (18" x 36")
PowerGrid 5.0	457.2 x 914.4 mm (18" x 36")

CERTIFICATIONS

INSTALLATION

Polished Concrete 5.0 / PowerGrid 5.0 Half Drop	Eero / Fargesia Bamboo / Heritage Wood / Kokutan 5.0 Ashlar Random	Fargesia Bamboo / Heritage Wood / Kokutan 5.0 Herringbone
--	---	--

CE MARKING

--	--	--	--	--	--	--	--	--	--