URBAN COLLECTIVE 2.0

Milliken

Citizen / On Bloc

Construction	Tufted, Luxury Textured Loop Pile
Face Fibre	100% Nylon 6 including 80% ECONYL $^{\circ}$ made with 100% regenerated fibre
Soil Release	StainSmart® for soil release, liquid repellence
Finished Face Weight	880 g/m ²
Gauge	47.2 / 10 cm
Rows	39.3 / 10 cm
Tuft Density	185,500 /m ²
Finished Pile Height	3-5 mm avg.
Standard Backing	Comfort Plus® 90% Recycled Polyurethane cushion Available with TractionBack® on request
Nominal Total Thickness	11.9 mm
Tile Size	50 cm x 50 cm
Nominal Total Weight	4600 g/m ²
Tiles per Box	16 (4m ²)
•	

PERFORMANCE

Flammability (Euroclassification EN13501:1-2002)	Class Cfl – s1
Flammability (Radiant Panel ASTM-E-648)	Class 1
Flammability (Hot Metal Nut BS4790)	Low Radius of Char
Use Classification (EN 1307)	Class 33 Heavy Commercial Use
Static Electricity (ISO 6356)	Pass ≤ 2.0 KV Permanent Conductive Fibre
Impact Sound (ISO 10140-3)	33 dB
Sound Absorption (ISO354)	0.3 (H) Class D
Alpha s values	125Hz 0.04, 250Hz 0.07, 500Hz 0.43, 1000Hz 0.26, 2000Hz 0.37, 4000Hz 0.56

ENVIRONMENTAL

80% regenerated content yarn (including 40% post consumer)

90% Recycled content cushion backing

30% Recycled content by total product weight

Manufactured in ISO14001 certfied location using electricity from renewable sources

GuT & CRI Green Label Plus certified for indoor air quality

EPD verfied - BRE certified

Brick

WARRANTIES

15 year wear warranty Lifetime Antistatic guarantee Latent Defects guarantee

C_{fl}-s1

НСНО



Design Copyright - Milliken & Company. This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

12 0338-CPD-10040 EN 14041-2001