


# APOLLO

Construction:	Tufted 1/10" Loop
Pile Material:	100% PA6 Solution Dyed Nylon
Secondary Backing:	Back2Back : Modified bitumen
Total Weight:	Ca. 4.250g/m <sup>2</sup>
Pile Weight:	Ca. 480g/m <sup>2</sup>
Pile Above Backing:	Ca. 273g/m <sup>2</sup>
Total Height:	Ca. 6,0mm
Pile Height:	Ca. 2,5mm
Pile Density	Ca. 0,110g/cm <sup>2</sup>
Tuft Density:	Ca. 176.000/m <sup>2</sup>
Classification:	EN 1307 33 – LC1
Castor Chair Suitability:	EN 985 A : continuous use
Fire Resistant:	Bfl -s] ( EN 13501 – 1)
Fastness to Light:	ISO 105-B02 ≥ 7
Rubbing Fastness:	ISO 105-X12 ≥ 4
Colour Fastness to Water:	EN ISO 105-E01 ≥ 4
Thermal Resistance:	ISO 8302 – 0,067m <sup>2</sup> K/W
Impact Noise Rating:	ISO 10140 ΔLw: 24dB ISO
Sound Absorption:	ISO 354 aw: 0,15
Permanent Antistatic:	ISO 6356 ≤ 2kV
Transversal Resistance:	ISO/DIS 10965 ≤ 10 <sup>9</sup> Ohm
Size:	50 x 50cm
Packaging:	Box: 5m <sup>2</sup> - Pallet: 20 boxes
Dimensional Stability:	EN 986 max. 0,2%



F512/02

M01/17

