

CARNIVAL

Construction:	Tufted 1/10" Loop
Pile Material:	100% PA6 Solution Dyed
Secondary Backing:	Back2Back: Modified bitumen
Total Weight:	Ca. 4300g/m ²
Pile Weight:	Ca. 500g/m ²
Pile Above Backing:	Ca. 302g/m ²
Total Height:	Ca. 5,8mm
Pile Height:	2,6mm
Pile density:	Ca. 0,116g/m ³
Tuft Density:	Ca. 171.600/m ²
Classification:	EN 1307
Castor Chair Suitable:	EN 985
Certification NF-UPEC:	U3P3E1C0
Fire Resistance:	EN 1305 – 1
Fastness to Light:	ISO 105-B02
Rubbing Fastness:	EN ISO 105-X12
Colour Fastness to Water:	EN ISO 105-E01
Thermal Resistance:	ISO 8302
Impact Noise Rating:	ISO 10140
Sound Absorption:	ISO 354
Permanent Antistatic:	ISO 6356
Transversal Resistance:	ISO/DIS 10965
Size & Packing:	50cm x 50cm
Number of Colours:	14
Dimensional Stability:	EN 986
LEED®:	Product contributes toward satisfying credit 4.3 under LEED®.

Products are not reviewed under LEED®. LEED® credit requirements cover the performance of materials in aggregate, not the performance of individual products.
