

# CHOMATIC

---

Construction:	Tufted 1/10" Loop
Pile Material:	100% PA6 Aqualon
Secondary Backing:	Back2Back: Modified bitumen
Total Weight:	Ca. 4300g/m <sup>2</sup>
Pile Weight:	Ca. 530g/m <sup>2</sup>
Pile Above Backing:	Ca. 335g/m <sup>2</sup>
Total Height;	Ca. 6,0mm
Pile Height:	Ca. 2,8mm
Pile Density:	Ca, 0,120g/cm <sup>3</sup>
Tuft Density:	Ca. 160.000/m <sup>2</sup>
Classification:	EN 1307
Castor Chair Suitable;	EN 985
Certification NF-UPEC:	U3P3E1C0
Fire Resistance:	EN 13501 – 1
Fastness to Light:	ISO 105-B02
Rubbing Fastness:	EN ISO 105-X12
Colour Fastness to Water:	EN ISO 105-E01
Thermal Resistance:	ISO 8302
Impact Noise Rating:	ISO 10140
Sound Absorption:	ISO 354
Permanent Antistatic;	ISO 6356
Transversal Resistance:	ISO/DIS 10965
Size & Packing:	50cm x 50cm
Number of Colours:	45, Special colours possible
Dimensional Stability:	EN 986
LEED:	Product contributes toward satisfying Credit under LEED®.*

