

COMFORT

CONSTRUCTION

Production method:	ISO 2424	Tufting 1/10th Cut Pile
Primary backing:	ISO 2424	Nonwoven Polyester
Secondary backing:	ISO 2424	Bitumen with glass fibre
Pile Type:	ISO 2076	100% Polyamide 6 (Solution Dyed)
Yarn brand:		Meraklon
Number of tufts:	ISO 1763	195,000 / m ² ± 5%
Pile height:	ISO 1766	4.8 mm. ± 0.5mm
Total thickness:	ISO 1766	6.0 mm. ± 0.5mm
Pile weight:	ISO 1958	800 gr./m ² ± 5%
Total weight:	ISO 8543	4600 gr./m ² ± 10%
Pile density:	ISO 1959	0.120 gr./cm ³ ± 10%
Tile size:	ISO 3018	50 x 50 cm.
Colour range:		8

CLASSIFICATION

Wear resistance:	EN 1307	Class 33
------------------	---------	----------

ADDITIONAL

Permanent antistatic:		Yes
Walk on test:	EN 1815	< 2 Kv
Pass by IBM/ICL:		Yes
Radiant panel test:	ISO13501	Cfl-S1
Hot metal nut:	BS4790	Low radius of effects of ignition

FASTNESSES

Light fastness:	ISO 105 B02	6
Water fastness:	ISO 105 E01	4-5
Rub fastness:	ISO 105 X12	4-5

Issue No. 1.0
Date: 28.01.13

We reserve the right to amend the technical specifications.
Subject to slight colour and structural deviations.
Discount Carpet Tiles. Net Limited.