

# ECLIPSE

---

Construction:	Tufted Loop Pile Carpet Tiles (50cm x 50cm)
Yarn Type:	100% Polypropylene
Machine:	1/10 <sup>th</sup> Gauge
Primary:	100gsm Non-Woven Polyester
Finished pile Weight (+/- 0.5%) BS 4223:	550gm/m <sup>2</sup>
Precoat Weight:	750gm/m <sup>2</sup>
Backing Weight:	3.,00gm/m <sup>2</sup>
Total Carpet Weight (+/- 10%) BS 4223:	4,400gm/m <sup>2</sup>
Backing Material:	Oxidised Bitumen with Spun Bonded Secondary
Reinforcement:	Glass Tissue for stability
Flammability:	BS 4790 Hot Metal Nut Test Low radius of Char, less than 35mm
Static:	Below 2000 volts, i.e. below the level of human sensitivity
Castor Wheel Test:	Overall r value 2.9
Dimensional Stability:	Passes Aachen DIN 54318
Light Fastness:	BS 1006 1990 BO2 (Better than 6 : Scale bad=1 to good=8)
Shampoo Fastness:	BS 1006 UK – TB 1990 : 4-5 Wool 5 All Other Fibres (5
represents no change)	
Rubbing Fastness:	BS 1006 x 12 1990 : West 5 : Dry 4-5 ( 5 represent no change)

---

Issue No. 1.0  
Date: 28.01.13

We reserve the right to amend the technical specifications.  
Subject to slight colour and structural deviations.  
Discount Carpet Tiles. Net Limited.

