

ELEMENTS II

DESCRIPTION

Construction:	Tufted Loop Pile
Machine:	1/10th Gauge
Fibre:	100% Solution Dyed Nylon
Primary Backing:	100 grms/square metre
Secondary Backing (Latex):	750 grms/square metre
Bitumen plus non-woven fleece:	2500 grms/square metre
Pile Weight:	500 grms/square metre
Total Weight:	4,3000 grms/square metre
Pile Height:	3.5 mm
Stitch Rate:	43.50 stitches per 10cm
Stitch Density:	171260 tufts/square metre
Tile Size:	50cm x 50cm
Tiles per Box:	20 or 5 square metres

PERFORMANCE

Flammibility:	BS 4790 Hot Metal Nut Test Low radius of char
Stroll Test:	BS ISO 6356 Less than 2 KV
Dimensional Stability:	Passes Aachen DIN 54318
Castor Wheel Test:	Pass r = 2.8 BS EN 985
Static Loading:	Not tested
Colour Fastness:	BS EN ISO 1056 (Scale bad 1 to good 8)
Fastness to Water:	BS EN ISO 1055
Fastness to Shampoo:	BS 1006 4-5
Fastness to Rubbing (Wet):	BS EN ISO 105 4-5
Fastness to Rubbing (Dry):	BS EN ISO 105 4-5

We reserve the right to amend the technical specifications.
Subject to slight colour and structural deviations.
Discount Carpet Tiles. Net Limited.