

# ELEMENTS CUT

---

## CONSTRUCTION

Production Method:	ISO 2424	Tufting 1/10 <sup>th</sup> Cut Pile
Primary Backing:	ISO 2424	Nonwoven Polyester
Secondary Backing:	ISO 2424	Bitumen with Glass Fibre
Pile Type:	ISO 2076	100% Polyamide 6 (Solution Dyed)
Yarn Brand:		Meraklon
Number of Tufts:	ISO 1763	195,000 / m <sup>2</sup> ± 5%
Pile Height:	ISO 1766	4.8 mm. ± 0.5mm
Total Thickness:	ISO 1766	6.0 mm. ± 0.5mm
Pile Weight:	ISO 1958	800 gr./m <sup>2</sup> ± 5%
Total Weight:	ISO 8543	4600 gr./m <sup>2</sup> ± 10%
Pile Density:	ISO 1959	0.120 gr./cm <sup>3</sup> ± 10%
Tile Size:	ISO 3018	50 x 50 cm.
Colour Range:		8
Wear Resistance:	EN 1307	Class 33

## ADDITIONAL TEST RESULTS

Permanent Antistatic:		Yes
Walk on Test:	EN 1815	< 2 kV
Pass by IBM/ICL:		Yes
Radiant Panel Test:	ISO13501	Cfl-S1
Hot Metal Nut:	BS4790	Low radius of effects of ignition

## FASTNESSES

Light Fastness:	ISO 105 B02	6
Water Fastness:	ISO 105 E01	4-5
Rub Fastness:	ISO 105 X12	4-5

---

Issue No. 1.0  
Date: 28.01.13

We reserve the right to amend the technical specifications.  
Subject to slight colour and structural deviations.  
Discount Carpet Tiles. Net Limited.