

# ELITE PRISMATIC

Construction:	Tufted 1/10" Loop
Pile Material:	100% PA6 Solution Dyed Aqualon
Secondary Backing:	Back2Back: Modified bitumen
Total Weight:	Ca. 4300g/m <sup>2</sup>
Pile Weight:	Ca. 540g/m <sup>2</sup>
Pile Above Backing:	Ca. 330g/m <sup>2</sup>
Total Height:	Ca. 6,4mm
Pile Height:	Ca. 2,9mm
Pile Density:	Ca. 0,114g/cm <sup>3</sup>
Tuft Density:	Ca. 156.000/m <sup>2</sup>
Classification:	EN 1307
Castor Chair Suitability:	EN 985
Fire Resistance:	EN 13501-1
Fastness To Light:	ISO 105-B02
Rubbing Fastness:	EN ISO 105-X12
Colour Fastness To Water:	EN ISO 105-E01
Thermal Resistance:	ISO 8302
Impact Noise Rating:	ISO 10140
Sound Absorption:	ISO 354
Permanent Antistatic;	ISO 6356
Transversal Resistance:	ISO/DIS 10965
Size & Packing:	50cm x 50cm
Number of Colours:	7
Dimensional Stability:	EN 986
LEED <sup>®</sup> :	Product contributes toward satisfying Credits under LEED <sup>®</sup> . *

