

WOOD EMOSS



TECHNICAL DATA	TECHNISCHE DATEN	DONNEES TECHNIQUES	TECHNISCHE SPECIFICATIE	FICHA TECNICA	NORM	NOUVEAU WOOD EMOSS
Type of flooring	Belagsart	Type de revêtement	Aard van vloerbedekking	Tipo de suelo	EN ISO 10582	Heterogen, PVC - registered embossing
Surface treatment	Oberflächenvergütung	Traitement de surface	Oppervlakte coating	Tratamiento de superficie		PU
Size	Abmessungen	Dimensions	Afmetingen	Dimensiones	EN ISO 24342	17.78 x 121.92cm
Total thickness	Gesamtstärke	Epaisseur totale	Totale dikte	Espesor total	EN ISO 24346	2.5 mm
Wearlayer thickness	Nutzschichtdicke	Epaisseur de la couche d'usure	Dikte toplaag	Espesor capa de uso	EN ISO 24340	0.55 mm
Beveled edges	Gefaste Kanten	Châînefrein	Facetrand	Biselados	4 x	Yes / Ja / Oui / Ja / Si
Performance classification	Beanspruchungsklasse	Classement européen	Gebruiksklasse	Utilizar la clase Europea	EN ISO 10874	23, 33, 42
Weight per m² (approx.)	Gesamtgewicht pro m² (ca.)	Poids par m²	Gewicht per m2	Peso/ m²	EN ISO 23997	4.6 kg
Number of pieces per carton	Verpackungseinheit pro Karton	Nombre de pièces p. carton	Aantal stuks per doos	Cantidad de laminas/Caja		18 ≈ 3.90 m²
Number of cartons per pallet	Anzahl Kartons per Palette	Nombre de cartons p. palette	Aantal dozen per pallet	Caja/ paleta		60
Wear group	Abriebbeständigkeit	Groupe d'abrasion	Slijtvestheid	Grupo de abrasión	EN 660-2	Group T
Residual indentation	Resteindruck	Poinçonnement statique rémanent	Restindruk	Punzonamiento	EN ISO 24343-1	Conforms/Konform/ Conforme/konform/ Se conforma
Fire	Brandklasse	Classement feu	Brandklasse	Fuego	EN 13501-1	Bfl- S1
Reduction transmission impact noise	Trittschallverbesserungsmass	Amélioration aux bruits d'impact	Impact geluidreductie	Reducción del sonido del impacto	EN 140-8	5 dB
Color fastness	Lichtechtheit	Tenue à la lumière	Kleurechtheid	Solidez del color	ISO 105-B02	≥6
Anti-slip classification	Rutschhemmung	Résistance aux glissements	Anti slip klasse	Resistencia al deslizamiento	DIN 51130	R 9
Resistance to chemicals	Chemikalienbeständigkeit	Résistance aux produits chimiques	Chemicalenbestendigheid	Resistencia a los agentes químicos	EN 423	Unchanged/Unverändert/Inchangée/ Onveranderd/Sin cambios*
Suitable for floor heating	Eignung Fussbodenheizung	Aptitude au chauffage par le sol	Geschikt voor vloerverwarming	Conveniente por suelo radiante		Yes / Ja / Oui / Ja / Si
Castor chair suitability	Stuhllolleneignung	Résistance aux sièges à roulettes	Geschiktheid voor stoelrollen	Resistencia a sillas de ruedas	EN 425	Yes/Ja/Si (Type W- soft)
Emission AgBB	Emissionen AgBB	Emission AgBB	Emissies AgBB	Emisión AgBB		Conforms/Konform/ Conforme/konform/ Se conforma
DoP (Declaration of performance)	DoP (Leistungserklärung)	DoP (déclaration des performances)	DoP (Prestatieverklaring)	DoP Declaración de Prestaciones		052310214
Cleaning and maintenance	Reinigungs- u. Pflegeempfehl.	Nettoyage et entretien	Reinigen en onderhoud	Limpieza y mantenimiento		CC-Dr. Schutz (or similar)

- * during brief exposure to regular household products
- * bei kurzzeitiger Einwirkung von gebräuchlichen, haushaltsüblichen Mitteln
- * lors de brèves expositions à des produits d'entretien ménagers habituels
- *bij kortstondig gebruik van reguliere huishoudproducten
- * Durante la breve exposición a productos de uso doméstico regular

