

# FANTASIA

---

## CONSTRUCTION

Production method:	ISO 2424	Tufting 1/12 <sup>th</sup> Pattern structured loop
Primary backing:	ISO 2424	Nonwoven Polyester/Nylon
Secondary backing:	ISO 2424	Bitumen with glassfibre
Pile Type:	ISO 2076	100% Polyamide 6,6
Yarn brand:		Antron Lumena
Number of tufts:	ISO 1763	227,000/m <sup>2</sup> ± 5%
Pile height:	ISO 1766	2.5mm. ± 0.5mm
Total thickness:	ISO 1766	6.0mm. ± 0.5mm
Pile weight:	ISO 1958	650gr./m <sup>2</sup> ± 5%
Total weight:	ISO 8543	4140gr./cm <sup>2</sup> ± 10%
Pile density:	ISO 1959	0.186gr./cm <sup>2</sup> ± 10%
Colour range:		12
Wear resistance:	EN 1307	Class 4
Castor chair test:	EN 985/A	Pass > 2.4
Permanent antistatic:		Yes
Walk on test:	EN 1815	< 2kV
Pass by IBM/ICL:		Yes
Radiant panel test:	ISO13501	Cfl-S1
Hot metal nut:	BS4790	Low radius of effects of ignition

## FASTNESSES

Light fastness:	ISO 105 B02	6
Water fastness;	ISO 105 E01	4-5
Rub fastness	ISO 105 X 12	4-5

---

We reserve the right to amend the technical specifications.  
 Subject to slight colour and structural deviations.  
 Discount Carpet Tiles. Net Limited.