

# FUTUREPROOF

Construction:	Tufted 1/10" Loop
Pile Material:	100% ECONYL <sup>®</sup> yarn
Secondary Backing:	Back2Back: Modified bitumen
Total Weight:	Ca. 4400g/m <sup>2</sup>
Pile Weight:	Ca. 600g/m <sup>2</sup>
Pile Above Backing:	Ca. 395g/m <sup>2</sup>
Total Height:	Ca. 6.3mm
Pile Height:	Ca. 3,2mm
Pile Density:	Ca, 0,123g/cm <sup>3</sup>
Tuft Density:	Ca. 160.000/m <sup>2</sup>
Classification:	EN 1307
Castor Chair Suitable;	EN 985
Certification NF-UPEC:	U3P3E1C0
Fire Resistance:	EN 13501 – 1
Fastness to Light:	ISO 105-B02
Rubbing Fastness:	EN ISO 105-X12
Colour Fastness to Water:	EN ISO 105-E01
Thermal Resistance:	ISO 8302
Impact Noise Rating:	ISO 10140
Sound Absorption:	ISO 354
Permanent Antistatic;	ISO 6356
Transversal Resistance:	ISO/DIS 10965
Size & Packing:	50cm x 50cm
Number of Colours:	36
Dimensional Stability:	EN 986
LEED <sup>®</sup> :	Product contributes toward satisfying Credit 4.3 under LEED <sup>®</sup> .

