

LINEAR

Production method	ISO 2424	Tufted 1/10" Loop Pile
Primary backing	ISO 2424	Non-woven polyester
Secondary backing	ISO 2424	Bitumen with glassfibre 3kg/m ²
Pile composition	ISO 2076	100% solution dyed polypropylene
Number of tufts	ISO 1763	181,162 tufts /m ²
Pile height	ISO 1766	± 3.5mm
Total thickness	ISO 1765	± 6.3mm
Pile weight	ISO 2424	± 550 gr./m ²
Total weight	ISO 8543	± 4390 gr./m ²
Product dimension	ISO 3018	50 cm x 50 cm
Tiles per box		20 (5m ²)
Colours		20
Wearing rating	EN 1307	Class 32
Castor chair	EN 985 / A	> 2.4
Permanent antistatic		Yes
Walk on test	ISO 6356	< 2 kV
Horizontal resistance	ISO 10965	≤ 10 ⁹ Ω
Vertical resistance	ISO 10965	≤ 10 ⁹ Ω
Dimension stability	ISO 2551	< 0.2%
Impact noise reduction	ISO 140-8	24 dB
Sound absorption	ISO 354	500 1000 2000 4000 Hz 0,07 0,19 0,28 0,32
Fire retardancy	ISO 13501-01	Cfl-S!
Light fastness	ISO 105 B02	≥ 6
Water fastness	ISO 105 E01	5
Rub fastness	ISO 105 X12	5

Issue No. 1.0
Date: 28.01.13

We reserve the right to amend the technical specifications.
Subject to slight colour and structural deviations.
Discount Carpet Tiles. Net Limited.

