

	Construction:	Tufted 1/10" Loop
	Pile Material:	100% PA6 Solution Dyed
	Secondary Backing:	Back2Back: Modified bitumen
	Total Weight:	Ca. 4300g/m²
	Pile Weight:	Ca. 500g/m²
	Pile Above Backing:	Ca. 302g/m²
	Total Height: `	Ca. 5,8mm
	Pile Height:	2,6mm
	Pile density:	Ca. 0,116g/m³
	Tuft Density:	Ca. 171.600/m²
	Classification:	EN 1307
	Castor Chair Suitable:	EN 985
	Certification NF-UPEC:	U3P3E1C0
	Fire Resistance:	EN 1305 – 1
	Fastness to Light:	ISO 105-B02
	Rubbing Fastness:	EN ISO 105-X12
	Colour Fastness to Water:	EN ISO 105-E01
	Thermal Resistance:	ISO 8302
	Impact Noise Rating:	ISO 10140
	Sound Absorption:	ISO 354
	Permanent Antistatic:	ISO 6356
	Transversal Resistance:	ISO/DIS 10965
	Size & Packing:	50cm x 50cm
	Number of Colours:	14
	Dimensional Stability:	EN 986
	LEED®:	Product contributes toward satisfying credit 4.3 under LEED®.
Products are not reviewed under LEED®. LEED® credit requirements cover the performation		der LEED®, LEED® credit requirements cover the performance of

Products are not reviewed under LEED®. LEED® credit requirements cover the performance of materials in aggregate, not the performance of individual products.