

REVIVE

Construction:	Tufted Loop Pile carpet Tile (50cm x 50cm)
Yarn Type:	100% Polypropylene
Machine:	1/10 th Gauge
Primary:	100gsm Non-Woven Polyester
Finished Pile Weight (+/- 0.5%) BS 4223):	550gm/m ²
Precoat Weight:	750gm/m ²
Backing Weight:	2,500gm/m ²
Total Carpet Weight (+/- 10%) BS 4223:	4,400gm/m ²
Backing Material:	Oxidised Bitumen with Spun Bonded Secondary
Reinforcement:	Glass Tissue for stability
Flammability:	BS 4790 Hot Nut Test Low radius of Char, less than 35mm
Static:	Below 2000 volts, i.e. below the level of human sensitivity
Castor Wheel Test:	Overall r value 2.4
Dimensional Stability:	Passes Aachen DIN 54318
Light Fastness:	BS 1006 1990 BO2 Better than 6 (Scale bad=1 to good=8)
Shampoo Fastness:	BS 1006 UK – TB 1990 : 4-5 Wool 5 All Other Fibres
Rubbing Fastness:	BS 1006 x 12 1990 ; Wet 5 : Dry 4-5 (5 represents to change)

We reserve the right to amend the technical specifications.
Subject to slight colour and structural deviations.
Discount Carpet Tiles. Net Limited.