

SHADOW

CONSTRUCTION

Production method:	ISO 2424	Tufting 1/12 th Pattern structured Cut/Loop
Primary backing:	ISO 2424	Nonwoven Polyester/Nylon
Secondary backing:	ISO 2424	Bitumen with glass fibre
Pile Type:	ISO 2076	100% Polyamide 6,6
Yarn brand:		Antron Lumena
Number of tufts:	ISO 1763	226,560 / m ²
Pile height:	ISO 1766	3.0mm. ± 0.5mm
Total thickness:	ISO 1766	6.7mm. ± 0.5mm
Pile weight:	ISO 1958	780gr./m ² ± 5%
Total weight:	ISO 8543	4620gr./m ² ± 10%
Pile density:	ISO 1959	0.177gr/cm ² ± 10%
Tile size:	ISO 3018	50 x50cm.
Colour range:		Colour development in progress

CLASSIFICATION

Wear resistance:	EN 1307	Class 4
------------------	---------	---------

ADDITIONAL TEST RESULTS

Castor chair test:	EN 985/A	Pass > 2.4
Permanent antistatic:		Yes
Walk on test:	EN 1815	< 2 kV
Pass by IBM/ICL		Yes
Radiant panel test:	ISO 13501	Cfl-S1
Hot metal nut:	BS 4790	Low radius of effects of ignition

FASTNESSES

Light fastness:	ISO 105 B02	6
Water fastness:	ISO 105 E01	4-5
Rub fastness:	ISO 105 X 12	4-5

We reserve the right to amend the technical specifications.
 Subject to slight colour and structural deviations.
 Discount Carpet Tiles. Net Limited.