

# SHIFT

Construction:	Tufted 1/12" Loop
Pile Material:	100% PA6 Solution Dyed Nylon
Secondary Backing:	Back2Back: Modified bitumen
Total Weight:	Ca. 4600g/m <sup>2</sup>
Pile Weight:	Ca. 680g/m <sup>2</sup>
Pile Above Backing:	Ca. 410g/m <sup>2</sup>
Total Height;	Ca. 7,7mm
Pile Height:	Ca. 3,7mm
Pile Density:	Ca, 0,100g/cm <sup>3</sup>
Tuft Density:	Ca. 197.500/m <sup>2</sup>
Classification:	EN 1307 – Class 33
Castor Chair Suitable;	EN 985 – A: Continuous use
Fire Resistance:	EN 13501 – 1 - Bfl-s1
Fastness to Light:	ISO 105-B02 - ≥7
Rubbing Fastness:	EN ISO 105-X12 - ≥4
Colour Fastness to Water:	EN ISO 105-E01 - ≥4
Thermal Resistance:	ISO 8302 - 0.091 m <sup>2</sup> K/W
Impact Noise Rating:	ISO 10140 - ΔLw: 25 dB
Sound Absorption:	ISO 354 - αw: 0,20
Permanent Antistatic;	ISO 6356 - ≤ 2 kV
Transversal Resistance:	ISO/DIS 10965 - ≤ 1 x 10 <sup>9</sup> Ohm
Size & Packing:	50cm x 50cm
Number of Colours:	13
Dimensional Stability:	EN 986 –max 0.2%
LEED <sup>®</sup> :	Product contributes toward satisfying Credits under LEED <sup>®</sup> .*

