

SPACE

Construction:	Tufted Loop Pile Carpet Tile (50cm x 50cm)
Yarn Type:	100% BCF Nylon - space dyed
Yarn Count:	2700 dTex
Pitch:	39.4/10 cm
Machine:	1/10th Gauge
Pile Height(above backing +/- 0.5 mm) BS 4223:	3.5mm
Finished Pile Weight (+/- 0.5%) BS 4223:	530gm/m ²
Backing Material:	Bitumen and Spun Bond and Glass
Coated Backing:	Antistatic SBR latex
Total Carpet Weight (+/- 10%) BS 4223:	4380gm/m ²
Total Carpet Thickness (+/- 10%) BS 4223:	7.5mm
Flammability BS 5287:	If ignited with small ignition source, this product will not spread flame under normal conditions.
Hot Metal Nut BS 4790:	Low radius of effect of ignition.
Methenamine Pill BS 6307:	Pass
Chemicals:	Resists most common contaminants.
Biological Attack:	Insect and Rot Proof.
Static Electricity:	Very low propensity to static. Computer anti-static
IBM/ICL	
Colour Fastness BS 1006:	NEC is colour fast. Light 5-6
Castor Chair Rating BS EN 985:	Pass 2.9

We reserve the right to amend the technical specifications.
Subject to slight colour and structural deviations.
Discount Carpet Tiles. Net Limited.