

# SPECTRA

---

## CONSTRUCTION

|                    |          |                                    |
|--------------------|----------|------------------------------------|
| Production method; | ISO2424  | Tufting 1/12 Ptern structures loop |
| Primary backing;   | ISO 2424 | Nonwoven Polyester/Nylon           |
| Secondary backing; | ISO 2424 | Bitumen with glassfibre            |
| Pile Type;         | ISO 2076 | 100% Poyamide 6,6                  |
| Yarn brand;        |          | Antron Lumena                      |
| Number tufts;      | ISO 1763 | 217,000/m <sup>2</sup> ± 5%        |
| Pile height;       | ISO 1766 | 2.5mm. ± 0.5mm                     |
| Total thickness;   | ISO 1766 | 6.0mm. ± 0.5mm                     |
| Pile weight;       | ISO 1958 | 670gr./m <sup>2</sup> ± 5%         |
| Total weight;      | ISO 8543 | 4160gr./m <sup>2</sup> ± 10%       |
| Pile density;      | ISO 1959 | 0.186gr./cm <sup>2</sup> ± 10%     |
| Tile size;         | ISO 3018 | 50 x 50cm.                         |
| Colour range;      |          | 12                                 |

## CLASSIFICATION

|                  |         |         |
|------------------|---------|---------|
| Wear resistance; | EN 1307 | Class 4 |
|------------------|---------|---------|

## ADDITIONAL

|                       |           |                                   |
|-----------------------|-----------|-----------------------------------|
| Castor chair test;    | EN 985/A  | Pass > 2.4                        |
| Permanent antistatic; |           | Yes                               |
| Walk on test;         | EN 1815   | < 2 kV                            |
| Pass by IBM/ICL;      |           | Yes                               |
| Radiant panel test;   | ISO 13501 | Cfl-S1                            |
| Hot metal nut;        | BS 4790   | Low radius of effects of ignition |

## FASTNESSES

|                 |              |     |
|-----------------|--------------|-----|
| Light fastness; | ISO 105B02   | 6   |
| Water fastness; | ISO 105 E01  | 4-5 |
| Rub fastness;   | ISO 105 X 12 | 4-5 |

Issue No. 1.0  
Date: 28.01.13

We reserve the right to amend the technical specifications.  
Subject to slight colour and structural deviations.  
Discount Carpet Tiles. Net Limited.