



TRIO

Construction:	Tufted 1/10" Loop
Pile Material:	100% PA 6 Aqualon
Secondary Backing:	Back2Back: Modified bitumen
Total Weight:	Ca. 4700g/m ²
Pile Weight:	Ca. 740g/m ²
Pile Above Backing:	Ca. 418g/m ²
Total Height;	Ca. 7,2mm
Pile Height:	Ca. 3,5mm
Pile Density:	Ca. 0,116g/cm ³
Tuft Density:	Ca. 158.500/m ²
Classification:	EN 1307 – Class 33
Castor Chair Suitable:	EN 985 – Continuous use
Fire Resistance:	EN 13501 – 1 - Bfl-s1
Fastness to Light:	ISO 105-B02 - ≥7
Rubbing Fastness:	EN ISO 105-X12 - ≥4
Colour Fastness to Water:	EN ISO 105-E01 – ≥4
Thermal Resistance:	ISO 8302 – 0.050m ² K/W
Impact Noise Rating:	ISO 10140 – 36dB
Sound Absorption:	ISO 354 – 0.15
Permanent Antistatic;	ISO 6356 – 2kV
Size & Packing:	50cm x 50cm
Number of Colours:	7
Dimensional Stability:	EN 986 – max 0.2%
LEED®:	Product contributes toward satisfying Credits under LEED®.*

