



paragon  
CARPET TILES



Experience Carpet Tiles

---

WORKSPACE LINEAR

---

# Workspace Linear

BREEAM® 'A+' Rated

MADE IN  
BRITAIN



Suitable for office,  
commercial, retail,  
schools, colleges,  
and leisure

Heavy Contract  
100% Solution  
Dyed Nylon /  
Space Dyed Nylon

10 year  
Warranty

Available in  
15 colourways

600 gsm  
Pile Yarn Weight

BREEAM 'A+' Rated  
Total recycled  
content of up  
to 50%

Workspace linear



Nobu Grey

	Style	Tufted Loop Pile Tile 1/10" gauge
	Yarn Construction	100% solution dyed nylon/space dyed nylon
	Pile Yarn Weight	600 gsm
	Pile Height	3mm
	Total Weight	4380 gsm
	Total Thickness	6mm
	Backing	Bitumen
	Dimensions	50cm x 50cm
	Wear Classification	Heavy Contract
	Anti-static	< 2kV body voltage Suitable for use with computers
	Colour Fastness	To Light BS EN (ISO105 - B02) 6 To Water BS EN (ISO105 - E01) 4 - 5
	Flammability Flammability	Euroclass (BS EN ISO 9239-1) (BS EN ISO 11925-2) Bfl - s1
	Castor Chair Test	> 2.9 Suitable for continuous use BS EN 985 /
	Warranty	10 Year Warranty
	VOC Content	E1 in relation to EN 14041:2004

Workspace linear



Farfield Park  
Manvers  
Wath-upon-Dearne  
Rotherham, S63 5DB

T. +44 (0) 1709 763 839  
F. +44 (0) 1709 763 813  
E. sales@paragon-carpets.co.uk  
W. www.paragon-carpets.co.uk



BREEAM® 'A+' Rated

Islington Tunnel

## INSTALLATION

Sub floors should be clean, dry and flat and prepared in accordance with BS5325. Timber floors should be covered with plywood or other appropriate sheet materials. For tiles use F Ball tackifier F41 or Laybond 79. Tiles may be laid tessellated or broadloom. Tiles should be allowed to condition for a minimum of 24 hours at the expected temperature and humidity prevailing when the building is in use. Further installation information is available from the Paragon Sales Office.

## COLOUR

For technical reasons, as with all textile materials, it may not be possible to colour match from different batches. Orders requiring colour match should be placed at the same time. Production may therefore show variations to the sample card.

## MAINTENANCE

It is recommended that a maintenance schedule be initiated from the date of installation to achieve maximum life expectancy of the product. Regular vacuum cleaning with a twin motored upright vacuum cleaner is essential. All spillages and stains should be attended to immediately. For detailed information, please consult the Paragon cleaning and maintenance guide. It is imperative that all internal carpets are well protected from outside soiling and moisture by the use of barrier matting such as Mat.Works, also available from Paragon.



Farfield Park  
Manvers  
Wath-upon-Dearne  
Rotherham, S63 5DB

T. +44 (0) 1709 763 839  
F. +44 (0) 1709 763 813  
E. sales@paragon-carpets.co.uk  
W. www.paragon-carpets.co.uk



