


Jazz Loop and Jazz Lines



	Standard Ref	Tiles
Product name		Jazz
Construction		Tufted Loop Pile
Fibre type		100% SD Meraklon Nylon
Primary Backing		100 g/ ms
Secondary Backing		750 g/ ms
Bitumen Plus non-woven fleece		3,000 g/ ms
Pile Weight		500 g/ ms
Total Weight		4,3000 g/ ms
Pile Height		3.5 mm
Stitch Rate		43.50 stitches per 10cm
Stitch Density	BS 8493:2008	171260 tufts/sq m
Tile Size	BS 4939/ISO 3416	50cm x 50cm
Tiles per box	BS ISO 2094	20 or 5 sq m
Flammability	BS 4790	HMN Pass LRC
Stroll Test	BS ISO 6356	Less than 2 KV
Dimensional Stability	DIN 54318	Pass
Castor wheel test	BS EN 985	Pass r = 2.8
Colour Fastness	BS EN ISO 105	6 (Scale bad 1 to good 8)
Fastness to Water	BS EN ISO 105	5
Fastness to Shampoo	BS 1006	4-5
Fastness to rubbing (wet)	BS EN ISO 105	4-5
Fastness to rubbing (dry)	BS EN ISO 105	4-5



Installation

All aspects of sub floor preparation and flooring installation must be carried out in accordance with BS5325:2001 Code of Practice for installation of Textile Floorcoverings. Sheet carpet should be fully adhered with approved adhesives. The products should be allowed to acclimatise for 24 hours at room temperature (15-20°C) prior to installation. We recommend that the tiles are installed by turning alternate tiles through 90° to obtain a chequerboard pattern and should be adhered with approved adhesives. During both planning and installation, consideration must be given to batch matching and pile direction. For further information contact the Rawson Carpet Sales Team.

Maintenance

A regular maintenance programme is always recommended. Use a suction type of vacuum cleaner for daily maintenance. Periodic shampooing and cleaning by a professional cleaning company should be carried out to keep floorcoverings in good condition. Do not use petrol or similar solvents on these products. It is strongly recommended that to prevent excessive flattening, use cups and pads under heavy furniture and chair mats under castor chairs. With tile products, traffic paths can be avoided by interchanging the tiles as necessary.

Environmental information

- Rawson products achieve either A or A+ across BREEAM defined building regulations. For specific rating, please refer to www.breeam.co.uk
- All Rawson carpet sheet and tile are made in the UK.
- Wherever possible, raw materials are sourced in the UK.
- Continuous assessment and improvement of manufacturing process is implemented to minimise use of raw materials/power.



Technical specification sheet:

All weights and thickness quoted +/- 10%. Due to batch to batch variation, production material may vary in colour from that shown on the sample card.



RAWSON
CARPET SOLUTIONS